

Indicators

| Product | Mounting | Display Height | Page |
|--------------------------------|--------------------------------------|---|------------|
| EZ-ZONE® PM | 1/32, 1/16, 1/8, 1/4 DIN front panel | Upper/Left: 0.30 to 0.80 in. (8 to 20 mm) Lower/Right: 0.22 to 0.50 in. (6 to 13 mm) | 377 |
| EZ-ZONE RUI and Gateway | 1/16 DIN front panel | Upper: 0.40 in. (10 mm) Lower: 0.24 in. (6 mm) | 378 |
| SERIES TM | DIN-rail, front panel, chassis | 0.28 in. (7 mm) | 379 |





Indicators

EZ-ZONE® PM

The EZ-ZONE® PM panel mount controller offers control options that reduce system complexity and thermal loop ownership cost. It can be ordered as a PID controller, an over/under limit controller or its functions can be combined into an integrated controller. An option to integrate a high amperage power controller output with a high-performance PID controller and an over/under limit controller in one space-saving, panel mount package is also available. Many communications options are offered to support connectivity needs.

Because the EZ-ZONE PM controller is highly scalable, pay only for what is needed. This controller is available in 1/32, 1/16, 1/8 and 1/4 DIN panel mount packages. The EZ-ZONE PM controller is easy to use and is ideal for PID, over/under limit or integrated controller needs.

Features and Benefits

Integrated PID and limit controller

- Reduces wiring time and termination complexity compared with connecting discrete products
- Decreases required panel space
- Lowers installation costs
- Increases user and equipment safety for over/under temperature conditions

High amperage power control output

- Drives 15 ampere resistive loads directly
- Reduces component count
- Decreases cost of ownership

Current monitoring

- Detects heater current flow and provides alarm indication of a failed output device or heater load

Serial communication capabilities

- Provides a wide range of protocol choices including Modbus® RTU, EtherNet/IP™, Modbus® TCP, PROFIBUS DP and DeviceNet™
- Supports network connectivity to a PC or PLC

Dual-channel controller

- Provides two PID controllers in one space-saving package



Enhanced control options

- Easily handles complex process problems such as cascade, ratio, differential, square-root, motorized valve control without slidewire feedback, wet-bulb/dry-bulb, compressor control and peltier loads

Advanced PID control algorithm

- Offers TRU-TUNE®+ adaptive control to provide tighter control for demanding applications
- Provides auto-tune for fast, efficient startup

Configuration communications with software

- Includes Watlow standard bus communications and EZ-ZONE configurator software
- Saves time and improves reliability of controller setup

For detailed product and ordering information, see the full EZ-ZONE PM product section located on pages 249 through 257.

Indicators

EZ-ZONE RUI and Gateway

The EZ-ZONE Remote User Interface (RUI and communications gateway) can be utilized as a communication gateway device to save cost, space and wiring when digital communications is being used with two or more EZ-ZONE controllers. The EZ-ZONE RUI can also serve as a display for showing all parameter values for up to 16 EZ-ZONE controllers, again saving cost, space and wiring expenses.

Indicator Features and Benefits—Remote User Interface (RUI)

Single user interface device or location to access multiple controllers

- Easy accessibility to all controllers and all parameters from a central location by using one RUI display
- Reduces component material costs by using a single RUI to display multiple control zones
- Eliminates cost and complexity from bringing all controller related input and output wiring to the front panel

Flexible use of a display interface

- Can be used when needed during normal machine production, for OEM prototype design purposes or for remote troubleshooting scenarios
- Ability to use more than one RUI indicator to display additional data including temperature and current (ammeter) to improve user system interface

Communications Gateway Features and Benefits

A single RUI and gateway provides field bus access for up to 16 EZ-ZONE controllers

- Lowers solution cost when field bus communications is required for multiple loops

Expand communication protocols to all EZ-ZONE controllers

- Ability to utilize multiple communication protocols for different user preferences. Flex between different communication protocols while still maintaining a reduced level of inventory



Delivers multiple communication protocol options

- Ability to connect EZ-ZONE controllers to communication networks utilizing
 - Modbus® RTU
 - DeviceNet™
 - Ethernet/IP™
 - Modbus® TCP
 - PROFIBUS DP

Additional Features

EZ-ZONE P3T armor sealing system

- Complies with NEMA 4X, IP65 RUI
- Offers water and dust resistance, can be cleaned and washed down

EZ-KEY (RUI)

- Programmable EZ-Key is a functional key programmable by the user to perform simple one-touch operation of repetitive user activities

Compact package

- Reduces required panel size for 1/6 DIN
- Utilizes less depth behind panel allowing for mounting in tight spaces

Touch-safe package

- Complies with IP2X which increases safety for user

Agency approvals: UL® Listed, CSA, CE, RoHS, W.E.E., SEMI F47-0200, Class 1, Div. 2 rating on selected models

- Meets applications requiring agency approvals

For detailed product and ordering information, see the full EZ-ZONE RUI and Gateway product section located on pages 371 through 374.

Indicators

SERIES TM

The SERIES TM temperature indicator from Watlow provides an economical solution for applications requiring temperature monitoring and display. Square 1/8 DIN panel mount and DIN-rail mount packaging options are available. A red, four-character, seven-segment LED display indicates the process value. The microprocessor-based design provides significant improvements in performance, repeatability and accuracy over analog indicators.

The indicators are UL[®] approved and include CE approvals. Panel mount indicators include NEMA 4X/IP65 seal protection. Watlow's SERIES TM temperature indicators include industry leading service and support and are backed by a three-year warranty.

Features and Benefits

Four character LED display

- Improves accuracy

Multiple mounting options

- Minimizes installation time

Fahrenheit or Celsius operation with indication

- Offers application flexibility

Agency approvals

- Meets certification requirements/compliance

Microprocessor-based technology

- Ensures accurate repeatable indication

Typical Applications

- Food preparation
- Industrial machinery
- Packaging
- Plastics processing



Specifications

Operator Interface

- Four-digit, seven-segment LED displays, 7 mm (0.28 in.) high
- °F or °C indicator

Standard Conditions For Specifications

- Rated line voltage, 50 to 60Hz, 0 to 90% RH non-condensing, 15-minute warm-up
- Calibration ambient range: 77°F (25°C) ±3°C

Thermocouple Input

- Grounded or ungrounded
- Type E, J, K, T thermocouple types
- >10 MΩ input impedance
- 250 nV input referenced error per 1Ω source resistance

RTD Input

- 2-wire platinum, 100Ω
- DIN curve (0.00385 curve)
- 125 μA nominal RTD excitation current

Input Accuracy Span Range

| | | | |
|-----------|----------------|----|----------------|
| Type E: | -328 to 1470°F | or | -200 to 800°C |
| Type J: | 32 to 1382°F | or | 0 to 750°C |
| Type K: | -328 to 2282°F | or | -200 to 1250°C |
| Type T: | -328 to 662°F | or | -200 to 350°C |
| RTD (DIN) | -328 to 1472°F | or | -200 to 800°C |

Thermocouple Input Accuracy

- Calibration accuracy: ±1% of input accuracy span, ±1° at standard conditions and actual calibration ambient. Exception: Type T, ±2.4% of input accuracy span for -328 to 32°F (-200 to 0°C)
- Temperature stability: ±0.3° per degree change in ambient

Indicators

SERIES TM

Specifications (Continued)

RTD Input Accuracy

- Calibration accuracy $\pm 1\%$ of input accuracy span $\pm 1^\circ$ at standard conditions and actual calibration ambient
- Temperature stability: $\pm 0.2^\circ$ per degree change in ambient

Indication Ranges

| | | | |
|-----------|----------------|----|----------------|
| Type E: | -328 to 1470°F | or | -200 to 800°C |
| Type J: | -346 to 1900°F | or | -210 to 1038°C |
| Type K: | -454 to 2500°F | or | -270 to 1370°C |
| Type T: | -454 to 750°F | or | -270 to 400°C |
| RTD (DIN) | -328 to 1472°F | or | -200 to 800°C |

Agency Approvals

- CE^①, W.E.E.E., RoHS EU Directive (2002-95-EC)
- UL[®] 873 recognized temperature indicator, File # E43684
- UL[®] 197 reviewed for use in foodservice appliances
- Temperature indicator CSA 22.2 No. 24, File # 30586
- Front panel mount models with gasket
 - UL[®] 50 Type 4X indoor use only
 - NEMA 4X/IP65 approved

Terminals

- 0.25 in. (6.3 mm) quick connect, push on terminal or removable screw style terminal block

Power

- 24VAC +10%; -15%; 50/60Hz, $\pm 5\%$
- 120VAC +10%; -15%; 50/60Hz, $\pm 5\%$
- 230 to 240VAC +10%; -15%; 50/60Hz, $\pm 5\%$
- 10VA max. power consumption

Operating Environment

- 32 to 158°F (0 to 70°C)
- 0 to 90% RH, non-condensing
- Storage temperature: -40 to 185°F (-40 to 85°C)

Dimensions

- DIN-rail model can be DIN-rail or chassis mount
DIN-rail spec DIN 50022, 1.38 x 0.30 in. (35 x 7.5 mm)

| Style | Width | Height | Depth |
|----------------------|-----------------------|------------------------|---------------------------------------|
| DIN-rail | 3.08 in. (78.1 mm) | 4.42 in. (112.3 mm) | 3.57 in. (90.7 mm) |
| Square 1/8 DIN Panel | 2.85 in. (72.4 mm) | 2.85 in. (72.4 mm) | Behind panel 2.04 in. (51.7 mm) |

① See declaration of conformity.

Ordering Information

Indicator only, 4-character, 7-segment display

Part Number

| | | | | | | | |
|-----|--------------|---------|---------------------|---|---------|---------|------------------------|
| ① ② | ③ | ④ | ⑤ | ⑥ | ⑦ ⑧ ⑨ ⑩ | ⑪ ⑫ ⑬ ⑭ | ⑮ |
| TM | Power Supply | Package | Sensor Type & Scale | A | AAAA | AAAA | Overlay/Custom Options |

| ③ Power Supply | |
|----------------|---------------|
| B = | 120VAC |
| D = | 230 to 240VAC |
| F = | 24VAC |

| ④ Package | |
|-----------|---|
| 1 = | Panel mount, 1/8 in. DIN square - spade terminals |
| 2 = | DIN-rail mount - spade terminals |
| 5 = | Panel mount, 1/8 in. DIN square - screw terminals |
| 6 = | DIN-rail mount - screw terminals |
| A = | NEMA 4X panel mount, - spade terminals |
| C = | NEMA 4X panel mount, - screw terminals |

| ⑤ Sensor Type & Scale | |
|-----------------------|--------------------------------|
| H = | T/C Type J °F (-346 to 1900°F) |
| J = | T/C Type J °C (-210 to 1038°C) |
| K = | T/C Type K °F (-454 to 2500°F) |
| L = | T/C Type K °C (-270 to 1370°C) |
| M = | T/C Type T °F (-454 to 750°F) |
| N = | T/C Type T °C (-270 to 400°C) |
| P = | RTD °F (-328 to 1472°F) |
| R = | RTD °C (-200 to 800°C) |
| S = | T/C Type E °F (-328 to 1470°F) |
| T = | T/C Type E °C (-200 to 800°C) |

| ⑮ Overlay/Custom Options | |
|--------------------------|------------------------------|
| A = | Standard with Watlow logo |
| 1 = | Standard without Watlow logo |